

• Description

This 4-electrode sensor is designed for air quality monitoring to measure the low-concentration O₃ gas with ultra-high resolutions. The design optimizes the sensor sensitivity, accuracy and long-term stability and enables the sensor to detect O₃ variations at parts per billion (ppb) levels.

• Performance Characteristics

Nominal Range:	0 ~ 5 ppm
Maximum Overload:	20 ppm
Sensitivity (20°C):	-0.45 ± 0.20 µA/ppm
Response Time (T90):	≤ 60 s
Zero Signal (20°C):	< ±70 nA
Baseline Shift (-40°C ~ 50°C):	< 50 ppb (After compensation)
Resolution:	10 ppb
Linearity:	Linear up to 5 ppm
Bias Voltage:	0 mV

• Environmental

Temperature Range:	-40°C ~ 50°C
Pressure Range:	1 ± 0.1 atm
Humidity Range:	15% ~ 90%RH non-condensing

• Life Time

Long Time Output Drift:	< 10% signal/year
Recommended Storage Temp:	10°C ~ 30°C
Expected Operating Life:	3 years in clean air
Storage Life:	6 months in original packaging
Warranty:	24 months

• Intrinsic Safety Data

Max. Current at 20ppm O ₃ :	< 0.2 mA
Max. O/C Voltage:	1.3 V
Max. S/C Current:	< 1.0 A


• Physical Characteristics

Housing Material:	ABS
Weight (Nominal):	8 g
RoHS Compliance	

• Installation

Output signals from the sensor pins are different. Inappropriate use of the pins in product design will affect the sensor functionality. Exposure to high concentrations of solvent vapors should be avoided under any condition. Mechanical overstress may cause deformation or cracks of the plastic enclosure of the sensor. If the sensor is used in extreme environmental conditions, please contact us for more details.

• Product Dimensions



All dimensions in mm

All tolerances ±0.20mm unless otherwise stated

• Note


The performance data in this document are conducted by using SemeaTech recommended test circuitry and test environment at 20°C, 50%RH and 1 atm. Sensor performance varies under different environmental conditions. Please contact us if you need more details.

• Cross-Sensitivity Data

Gas	Concentration (ppm)	Output Signal (ppb O3 equivalent)
Carbon Monoxide	5	48.0
Nitric Oxide	5	38.0
Nitrogen Dioxide	5	5,000.0
Sulfur Dioxide	5	33.0
Ammonia	20	50.0
Ethylene	100	51.0
Hydrogen Sulfide	5	31.0
Chlorine	5	2,493.0
Hydrogen	100	7.0

Note: The cross sensitivities include but not limited to the above gases. It may also respond to other gases. The data in the table above may vary from different batches of sensors and the changes of test environment. Calibration using the gases that have the cross sensitivities to this sensor is not recommended.

• Temperature Data



• Safety Note

This sensor is designed to be used in certain instruments for life critical applications. To ensure the sensor functioning per its specifications inside the instrument, it is required to read the instrument user's guide carefully and comply with the calibration procedures by using certified target calibration gas before each use. Failure to do so may cause serious injury and fatality. Please do not open the sensor plastic enclosure because the electrolyte and other chemicals stored inside are harmful.

It is highly recommended for customers to validate the sensor performance using the document as a reference for their product designs or applications.

This product data sheet is used for reference only.

SemeaTech is committed to provide its customers the most accurate data based on its best knowledge. SemeaTech does not provide product warranty for failures of using its products in accordance with product specifications that are described in the data sheet, or other misuse, abuse, negligence to the product.